

# YOU GIVE US THE SPECIFICATIONS - WE PROVIDE THE SOLUTION

## From drive systems to complete solutions: take advantage of our versatility!

Our innovative door drive mechanisms can be combined with various profile systems, including retro fitting onto door leaves from other suppliers and a wide range of accessories.

Comfort? Safety and security? Design? Hygiene? Energy efficiency? Managed pedestrian-flows? For whatever you need a Gilgen automatic door, you can be sure of finding the right solution for your requirements in our wide range of products.

Not all entrances have the requirements as a simple entrance. This is why it is important, right from the planning stage, to take into account the functions that are likely to be needed. For example:

- Environment friendly (the green door leaves)
- Break-in prevention
- Fire prevention
- Smoke control
- Emergency exits
- Hermetically sealing doors



Customers of Gilgen automatic doors benefit from greater convenience, join them by choosing the right solution for your needs



# Optimum combinations

	Basic	Standard	Design Header 100 mm	Technology Header 140 mm	Heavy duty	Traditional	Curved	Folding
Drive systems	SLA *	SLX-M	SLX	SLX	SLX-V	SLM	SRM	FFM
<b>Profile systems</b>								
Profile system PSX (slimline)	●		●	●				
Profile system PSXP (slimline, with interlocking)	●	●						
Profile system PSA (light, with interlocking)	●	●	●	●				
Profile system PSF (transparent)	●	●						
Profile system PST (slimline and heat-insulated) <green wings>		●						
Profile system PSW (heat-insulated) <green wings>	●			●				
Profile system PS 90 (traditional)						●	●	●
Door leaves supplied by others	●	●	●	●	●	●		
<b>Telescopic solutions</b>								
		●		●		●		
<b>Fire and smoke screens</b>								
Fire-rated shutter (EI30/E30)		●		●	●			
Smoke-proof shutter CS200						●		
<b>Escape route solutions</b>								
Redundant *		●	●	●		●	●	●
Break Out			●			●		
CO 48 (France) *	●	●	●	●		●		
<b>Officially recognised anti-burglary protection</b>								
RC2		●						
RC3		●						
<b>Offic. recog. tightness (SLX-D) Header 180mm</b>								
				●				
<b>Door locking</b>								
Manual floor lock on plinth profile	●	●	●	●	●	●		●
Automatic locking in the drive mechanism	●	●	●	●	●	●	●	●
Multi-point locking FLUVERI manual **	●	●	●	●				
Multi-point locking FLUVERI automatic ***		●	●	●				
Automatic stay-bar locking CLS ***					●	●	●	

\* not available in all countries

\*\* the installation of a FLUVERI is possible with the profile systems PSX, PSXP, PST and PSW

\*\*\* the installation of a CLS is possible with the profile system PS90 and mandatory with fire-protection version EI 30 Design.